

Montée de version Postgresql

[SGBD](#), [BDD](#), [Postgresql](#), [upgrade](#)

Sauvegarde

```
sudo -u postgres pg_dumpall | gzip > peertube-$(date +%Y-%m-%d').sql.gz
```

```
pg_lsclusters
Ver Cluster Port Status Owner    Data directory          Log file
13  main     5432 online postgres /var/lib/postgresql/13/main
   /var/log/postgresql/postgresql-13-main.log
15  main     5433 online postgres /var/lib/postgresql/15/main
   /var/log/postgresql/postgresql-15-main.log
```

```
pg_dropcluster 15 main --stop
```

```
sudo pg_upgradecluster 13 main
```

```
Stopping old cluster...
Restarting old cluster with restricted connections...
Notice: extra pg_ctl/postgres options given, bypassing systemctl for start
operation
Creating new PostgreSQL cluster 15/main ...
/usr/lib/postgresql/15/bin/initdb -D /var/lib/postgresql/15/main --auth-
local peer --auth-host scram-sha-256 --no-instructions --encoding UTF8 --lc-
collate en_US.UTF-8 --lc-ctype en_US.UTF-8
The files belonging to this database system will be owned by user
"postgres".
This user must also own the server process.
```

```
The database cluster will be initialized with locale "en_US.UTF-8".
The default text search configuration will be set to "english".
```

```
Data page checksums are disabled.
```

```
fixing permissions on existing directory /var/lib/postgresql/15/main ... ok
creating subdirectories ... ok
selecting dynamic shared memory implementation ... posix
selecting default max_connections ... 100
selecting default shared_buffers ... 128MB
selecting default time zone ... Europe/Paris
creating configuration files ... ok
running bootstrap script ... ok
performing post-bootstrap initialization ... ok
syncing data to disk ... ok
```

```
Copying old configuration files...
Copying old start.conf...
```

```
Copying old pg_ctl.conf...
Starting new cluster...
Notice: extra pg_ctl/postgres options given, bypassing systemctl for start
operation
Roles, databases, schemas, ACLs...
  set_config
  -----
(1 row)

  set_config
  -----
(1 row)

  set_config
  -----
(1 row)

  set_config
  -----
(1 row)

Fixing hardcoded library paths for stored procedures...
Upgrading database postgres...
Analyzing database postgres...
Fixing hardcoded library paths for stored procedures...
Upgrading database peertube_prod...
Analyzing database peertube_prod...
Fixing hardcoded library paths for stored procedures...
Upgrading database templatel...
Analyzing database templatel...
Stopping target cluster...
Stopping old cluster...
Disabling automatic startup of old cluster...
Starting upgraded cluster on port 5432...
```

Success. Please check that the upgraded cluster works. If it does,
you can remove the old cluster with
pg_dropcluster 13 main

Ver	Cluster	Port	Status	Owner	Data directory	Log file
13	main	5433	down	postgres	/var/lib/postgresql/13/main	/var/log/postgresql/postgresql-13-main.log
Ver	Cluster	Port	Status	Owner	Data directory	Log file
15	main	5432	online	postgres	/var/lib/postgresql/15/main	/var/log/postgresql/postgresql-15-main.log

pg_lsclusters

Ver	Cluster	Port	Status	Owner	Data directory	Log file
13	main	5433	down	postgres	/var/lib/postgresql/13/main	/var/log/postgresql/postgresql-13-main.log
15	main	5432	online	postgres	/var/lib/postgresql/15/main	/var/log/postgresql/postgresql-15-main.log

From:

<https://wiki.grohub.org/> - **Grohub wiki**

Permanent link:

<https://wiki.grohub.org/infrastructure/db/postgresql/upgrade?rev=1734444293>

Last update: **17/12/2024 14:04**

