

Miroir NodeJS

[packages](#), [apt](#), [aptly](#), [dépôt](#), [miroir](#), [nodejs](#)

Nous importons la clé GPG du dépôt

```
wget -q -O - https://deb.nodesource.com/gpgkey/nodesource.gpg.key | gpg --no-default-keyring --keyring trustedkeys.gpg --import
```

Si vous avez en retour ce genre de message



```
bash: gpg : commande introuvable
```

Il faut installer le paquet gnupg

```
sudo aptitude install gnupg
```

Nous créons le miroir

```
aptly mirror create -architectures=amd64 bookworm-nodejs-16x  
https://deb.nodesource.com/node_16.x bookworm main
```

Nous mettons à jour le miroir local

```
aptly mirror update bookworm-nodejs-16x
```

Nous créons un snapshot

```
aptly snapshot create bookworm-nodejs-16x-230719 from mirror bookworm-  
nodejs-16x
```

Nous publions le snapshot

```
aptly publish snapshot -distribution=bookworm-nodejs-16x -component=main  
bookworm-nodejs-16x-230719 debian
```

Si le dépôt a déjà été publié, nous “switchons” le snapshot

```
aptly publish switch bookworm-nodejs-16x debian bookworm-nodejs-16x-230719
```

Liens

- [dépôt Github Nodesources](#)

From:

<https://wiki.grohub.org/> - **Grohub wiki**

Permanent link:

<https://wiki.grohub.org/infrastructure/gestion-paquets/aptly/nodejs-mirror?rev=1689771708>

Last update: **19/07/2023 13:01**

